

# SUPER LONG LIFE COOLANT

## Green



### PRODUCT DESCRIPTION

Coolant based on ethylene glycol. The product is engineered for automotive cooling systems in accordance with the requirements of Japanese standard JIS K 2234. It is designed for use in passenger cars and commercial vehicles of various Japanese OEMs. The product contains a special carboxylate package of phosphates based additives and inhibitors for maximum protection of cooling systems of internal combustion engines, including those with application of aluminum alloys. The product forms a long-term protective film on internal surface of cooling system, thus protecting engine from freezing, overheat, cavitation, corrosion and contamination. The formulation is free from silicates, nitrates, borates and amines, thus it contributes to a decrease of hard deposits and to extension of service life of water pumps.

### APPLICATION

- TOTACHI® SUPER LONG LIFE COOLANT Green is recommended for cooling systems of gasoline and diesel engines of majority of Japanese car manufacturers: Honda, Nissan, Mitsubishi, Mazda, Suzuki, Subaru, Isuzu. The recommended drain interval of product for service fill is 3 years / 150 000 km.
- TOTACHI® SUPER LONG LIFE COOLANT Green is specially recommended for modern engines where the enhanced protection of aluminum against high-temperature corrosion is required.

### CUSTOMER BENEFITS

- TOTACHI® SUPER LONG LIFE COOLANT Green offers effective corrosion protection of engine parts made of iron (cast iron), aluminum, solders and copper alloys.
- TOTACHI® SUPER LONG LIFE COOLANT Green provides improved heat exchanging characteristics, which enhance performance of engines in highly loaded operating conditions.
- It possesses excellent compatibility with seal materials and rubber hoses, typically used by Japanese OEMs. The product can be easily mixed up with original Japanese coolants.



### MEETS SPECIFICATIONS AND REQUIREMENTS OF:

- ASTM D3306 for automotive services;
- JASO M325.

Before using this product make sure, it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TOTACHI® SUPER LONG LIFE COOLANT Green is supplied ready for use. It is not recommended to dilute the product with water for more than 10%. It is a good practice to flush cooling system before changing coolant.

For application in regions with mild climate use product with chill point of -40°C. For northern regions with severe cold climate use product with chill point of -50°C.

**TYPICAL TEST DATA**

CHARACTERISTICS	UNITS	-40°C	-50°C	METHOD
Appearance		Transparent liquid with no residue	Transparent liquid with no residue	P 5.2 ToR
Density at 20°C	g/cm <sup>3</sup>	1,077	1,084	GOST 18995.1, section 1
Swelling of rubber	%	2,7	2,9	GOST 9.030-7 p.1
Boiling point	°C	110	111	ASTM D1120
Chill point	°C	-40	-50	GOST 28084 p 4.4
Foaming: – Volume of foam after 5 minutes; – Foam stability	cm <sup>3</sup> sec	5 1	5 1	GOST 28084 p 4.6
Hydrogen ion exponent at 20°C	pH	7,7	8,1	GOST 22567.5
Color		Green	Green	visual

**STORAGE AND HANDLING GUIDELINES**

- Avoid exposing products to direct sunlight.
- Cans, packed in cardboard boxes, must be stored in dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors on pallets and racks.
- If stored outdoors drums should be placed sidewise to avoid accumulation of moisture.

**HEALTH, SAFETY AND ENVIRONMENT PROTECTION**

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential

hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

**ATTENTION:**

TOTACHI® SUPER LONG LIFE COOLANT Green *is poisonous and extremely hazardous if ingested.*

When changing coolant dispose off used product in accordance with local, regional or federal legislative provisions.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.